

FASERFIX SUPER

Drainage channels for extreme loads and high dynamic forces.

With the new
FASERFIX SUPER Angle Housing:

- 35 % more stability due to optimized construction
- 3 times better corrosion protection due to new zinc-magnesium coating



Racetrack „Sochi Autodrom“



FASERFIX SUPER

Drainage channels for extreme loads and high dynamic forces.

1 Requirements

Drainage channels in heavy traffic areas must

- withstand to extreme loads and high dynamic forces.
- be particularly stable to ensure a long-term security.
- be resistant to environmental influences. (frost, heat, moisture)

2 Application areas

- traffic areas for industry
- container terminals and ports
- roads and tunnels
- petrol stations and service areas
- airports


3 Solutions

Therefore FASERFIX SUPER channels offer solutions for any type of application in heavy duty traffic areas:

- large channels made from fibre-reinforced concrete (Basalt fibres)
- highly stable connection between angle housing and concrete
- optimal corrosion protection due to new zinc-magnesium coating of the steel angle housing
- stable gratings in the classes D 400, E 600 and F 900 according to DIN EN 1433
- grating securely located in 40 mm deep angle housings
- nominal sizes from 100 to 500 mm each in different heights
- boltless locking system SIDE-LOCK with additional eight bolt fixing per metre is possible
- safety joint for easy sealing



ADAC safe drive centre, Schlüsselfeld, Germany



Port in Gdansk, Poland



Airport Aulnat, France



Container terminal and port, Latvia



Traffic area for industry, Germany

**FASERFIX®
SUPER**

**FASERFIX®
KS**

**RECYFIX®
PLUS X**

**RECYFIX®
INC**

**RECYFIX®
MONOTEC**

**RECYFIX®
HICAP®F**

**FASERFIX®
POINT KS**

**FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC**

**SERVICE
CHANNEL**

KERBFIX 305

FASERFIX SUPER

Drainage channels for extreme loads and high dynamic forces.

Maximum security through reliable drainage systems for „Sochi Autodrome“ racetrack.

FASERFIX SUPER channels withstand high dynamic forces and extreme conditions as was demonstrated at the „Grand Prix of Russia“ on the racetrack in Sochi. The 4,400 m of built-in FASERFIX channels offer the racers a high level of security during the Grand Prix. The track also runs through the Olympic Park and was designed by German racetrack expert Hermann Tilke. The project management team from HAURATON and Tilke implemented the surface drainage together.




Particularly high demands:

- extreme loads on drainage channels due to suction effects of cars with maximum speeds over 300 km/h
- additional high loads by trucks and forklifts in the paddock, pit-lane and service areas
- exact installation of +/- 2 mm required
- problematic construction traffic resulted in requiring extremely high lateral stability of the channels
- upwardly open T and cross connections, so that the channels in the paddock can additionally be used as a cable channel
- installation of asphalt and paving construction directly to the channel corresponding to class D 400

Drainage channels:

- 2,225 m FASERFIX SUPER channels (in racetrack area, T16-T18), over 2,100 m FASERFIX SUPER 150 and 200 (paddock area) and RECYFIX 150 with slotted cover (racetrack, T16-T18)
- channels were installed with customized special components





**FASERFIX®
SUPER**

**FASERFIX®
KS**

**RECYFIX®
PLUS X**

**RECYFIX®
INC**

**RECYFIX®
MONOTEC**

**RECYFIX®
HICAP®F**

**FASERFIX®
POINT KS**

**FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC**

**SERVICE
CHANNEL**

KERBFIX 305

YOUR BENEFITS WITH **FASERFIX SUPER**

HIGH PERFORMANCE ANGLE HOUSING AND SIDE-LOCK

- 40 mm x 40 mm angle housing and recessed grating
- optimum corrosion protection due to zinc-magnesium coating
- extremely stable connection between steel frame and concrete channel body
- 16-fold fixing possibility of the grating per meter (8-fold **SIDE-LOCK** and 8-fold optional bolting).
- additional protection against longitudinal movements (anti-shear device)
- 90 % time saving when fastening with **SIDE-LOCK** (compared to conventional fastening)
- insertion or replacement of the grating possible without special tooling
- Revisable screw connection due to replaceable nut

= QUALITY ASSURED & COST SAVINGS



HIGH-TECH MATERIAL

- „Made in Germany“
- maximum stability through fibre-reinforced concrete (Basalt fibres) with low weight
- adheres well to foundation concrete (same coefficient with regard to thermal expansion)
- installation without grating possible
- fire resistance class A1 (not flammable) according to DIN 4102

= QUALITY- & PERFORMANCE ASSURED



HIGH STABILITY


- maximum lateral stability through extra thick walls compared to many competitors' products for additional security in extreme situations
- installation for asphalted surface up to class E 600 without concrete stretcher

= PERFORMANCE ASSURED



IDEAL FOR ...

applications with heavy loads and high dynamic forces up to class F 900, such as traffic areas for industry, roads and petrol stations.



FASERFIX SUPER

Drainage channels for extreme loads and high dynamic forces.

FASERFIX SUPER channels meet the requirements of DIN EN 1433 and are suitable for the following load categories:



Category A 15,
Load class 15 kN



Category B 125,
Load class 125 kN



Category C 250,
Load class 250 kN




Category D 400,
Load class 400 kN





Category E 600,
Load class 600 kN




Category F 900,
Load class 900 kN



Grating options FASERFIX SUPER Channels

	Mesh grating*	GUGI-Ductile iron mesh gratings*	Ductile iron gratings*	Solid covers*
Load categories				
C 250	300		300	
D 400			100, 150, 200, 300, 400, 500	
E 600		150, 200, 300, 400	500	150, 200, 300, 400, 500
F 900		100	150, 200, 300, 400, 500	

* sizes are nominal widths



Widths and heights of **FASERFIX SUPER**:



Nominal sizes	100			150			200			300			400			500		
																		
Type 01	190	190	190	240	255	195	290	305	240	390	415	345	490	540	455	590	630	540
Type 01E	-	-	-	240	255	195	290	305	240	390	415	345	490	540	455	-	-	-
Type 01H	-	-	-	-	-	-	-	-	-	390	630	545	490	630	545	-	-	-
Type 010	190	235	185	240	309	249	290	350	285	390	460	390	-	-	-	-	-	-
Type 010E	-	-	-	-	-	-	290	350	285	-	-	-	-	-	-	-	-	-
Type 020	190	285	235	-	-	-	290	400	335	390	510	440	-	-	-	-	-	-
Type 020E	-	-	-	240	369	309	290	400	335	-	-	-	-	-	-	-	-	-
available with built-in fall	-			x			x			x			-			-		





Width/Height/Inside height (in mm)

FASERFIX®SUPER 100

Channels

NEW FASERFIX®SUPER 100 with galvanised angle housings, up to load class F 900

Type 01, 1,0 m




	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	190	190	80	51,59	26000
Type 0105, 0,5 m	500	190	190	80	25,30	26049
Type 01L with outlet, DN/OD 110, 1,0 m*	1000	190	190	80	50,20	26045
Type 010, 1,0 m	1000	190	235	125	61,00	26042
Type 01005, 0,5 m	500	190	235	125	31,00	26050
Type 010L, with outlet, DN/OD 110, 1,0 m*	1000	190	235	125	59,70	26046
Type 020, 1,0 m	1000	190	285	175	70,47	26044
Type 02005, 0,5 m	500	190	285	175	38,00	26048
Type 020L, with outlet, DN/OD 110, 1,0 m*	1000	190	285	175	69,17	26047

* Position of the opening to the bottom of the channel. 100 mm from the centre of the hole (DN/OD 110) to the end of the channel.

FASERFIX®SUPER 100 with ductile iron angle housings, up to load class F 900

Type 010 with KTL-coated
ductile iron angle housing, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01 with KTL-coated ductile iron angle housing, 1,0 m	1000	190	190	80	52,42	1400
Type 010 with KTL-coated ductile iron angle housing, 1,0 m	1000	190	235	125	61,32	1442
Type 01005 with KTL-coated ductile iron angle housing, 0,5 m	500	190	235	125	31,21	1450
Type 020 with KTL-coated ductile iron angle housing, 1,0 m	1000	190	285	175	73,42	1444

Bolting required - see further accessories

FASERFIX®SUPER 100

Gratings

FASERFIX®SUPER 100, class D 400*



Ductile iron grating,
SW 94/16 mm, black,
with plastic caps, 0,5 m



Ductile iron grating
SW 94/16 mm, black,
KTL-coated, with plastic cap,
locked, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 94/16 mm, black, with plastic caps, 0,5 m	500	179	40	360	5,90	6063
Ductile iron grating SW 94/16 mm, black, KTL-coated, with plastic cap, locked, 0,5 m	500	179	40	360	6,10	6663
Ductile iron grating SW 94/16 mm, galvanised, with plastic caps, 0,5 m	500	179	40	360	5,97	6683

* Not for use across the carriageway of highways or motorways in moving traffic.

FASERFIX®SUPER 100, class F 900



GUGI-Ductile iron mesh
grating, MW 15/25 mm,
black, with plastic caps, 0,5 m



GUGI Ductile iron mesh
grating, MW 15/25 mm,
black, locked, KTL-coated,
with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
GUGI-Ductile iron mesh grating, MW 15/25 mm, black, with plastic caps, 0,5 m	500	179	40	494	7,60	6060
GUGI Ductile iron mesh grating, MW 15/25 mm, black, locked, KTL-coated, with plastic caps, 0,5 m	500	179	40	494	7,60	6660

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC


SERVICE
CHANNEL

KERBFIX 305


FASERFIX® SUPER 100

Accessories

Trash boxes



Trash box with galvanised mud bucket



Trash box with ductile iron angle housing and galvanised mud bucket

	Length mm	Width mm	Height mm	Weight kg	Item No.
NEW Trash box with galvanised mud bucket	500	190	522	59,00	26052
Trash box with ductile iron angle housing and galvanised mud bucket	500	190	522	62,06	1452


End caps



End cap closed, type 01



End cap closed, galvanised, type 010



End cap with horizontal PVC-U pipe outlet galvanised, type 010

	Length mm	Width mm	Height mm	Weight kg	Item No.
End cap closed, type 01	-	190	165	0,48	6081
End cap closed, galvanised, type 010	-	190	210	0,51	6082
End cap closed, galvanised, type 020	-	190	260	0,76	6083
End cap with horizontal PVC-U pipe outlet galvanised, type 010	-	190	210	0,66	6092
End cap with horizontal PVC-U pipe outlet galvanised, type 020	-	190	260	0,80	6093


The quality of stainless steel material corresponds to CNS 1.4301.

FASERFIX® SUPER 100

Further accessories



PVC-U pipe connection element
DN/OD 160



Mud bucket vertical made
of modified composite
for outlet DN/OD 110, black



Installation aid NW 100 (exclusively
for laying channels! For laying 2 pieces
are necessary) - due to security reasons
no return can be made

	Length mm	Width mm	Height mm	Weight kg	Item No.
Hexagon bolt with locking serration, stainless steel, M 10 x 50	-	-	-	0,04	99938
Caps for hexagon bolts	24	24	7	-	91100
Foul air trap DN/OD 110, with hole	-	-	103	0,24	964
PVC-U pipe connection element DN/OD 160	-	-	-	0,50	906
Mud bucket vertical made of modified composite for outlet DN/OD 110, black	100	100	85	0,04	40293
Universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	0,97	19051
Tubular pistol for universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	1,30	6891
Installation aid NW 100 (exclusively for laying channels! For laying 2 pieces are necessary) - due to security reasons no return can be made	-	-	-	1,60	705

**** Consumption for channel type 020: approx. 85 ml per joint.**

Factory-made services



Cutting to length
of NW 100



Cutting for gradient
for all nominal widths



Drilling of connecting holes
DN/OD 110



Fixing-system EP, empty pipe
in the channel bottom,
(2 pieces per metre)

	Length mm	Width mm	Height mm	Weight kg	Item No.
Cutting to length of NW 100	-	-	-	-	990
Mitre cuts NW 100 (price per cut, two cuts necessary)	-	-	-	-	995
Cutting for gradient for all nominal widths	-	-	-	-	890
Drilling of connecting holes DN/OD 110	-	-	-	-	972
Factory-made insertion of modified PP union connectors DN/OD 75 (incl. drilling)	-	-	-	-	981
Factory-made insertion of PVC-U union connectors DN/OD 110 (incl. drilling)	-	-	-	-	982
Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)	-	-	-	0,03	703
steel bars for fixing system EP (2 pieces per metre)	-	-	-	0,01	704

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL



KERBFIX 305

FASERFIX®SUPER 150

Channels

NEW FASERFIX®SUPER 150 with galvanised angle housings, up to load class F 900

Type 01, 1,0 m





	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	240	255	205	75,30	22000
Type 01L with hole, DN/OD 160, 1,0 m*	1000	240	255	205	77,00	22035
Type 0105, 0,5 m	500	240	255	205	37,00	22049
Type 010, 1,0 m	1000	240	300	272	84,40	22042
Type 010L with hole, DN/OD 160, 1,0 m*	1000	240	300	272	82,40	22036
Type 020, 1,0 m	1000	240	350	345	95,60	22044
Type 020L with hole, DN/OD 160, 1,0 m*	1000	240	350	345	93,60	22037
Type 01 E, 1,0 m	1000	240	255	223	80,00	22105

* Position of the opening to the bottom of the channel. 130 mm from the centre of the hole (DN/OD 160) to the end of the channel.

FASERFIX®SUPER 150

NEW FASERFIX®SUPER 150 with built-in fall 0.5 %, up to load class F 900

Type 1, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 1, 1,0 m	1000	240	255 - 260	212	76,21	22001
Type 2, 1,0 m	1000	240	260 - 265	220	77,12	22002
Type 3, 1,0 m	1000	240	265 - 270	227	78,03	22003
Type 4, 1,0 m	1000	240	270 - 275	235	78,94	22004
Type 5, 1,0 m	1000	240	275 - 280	242	79,85	22005
Type 6, 1,0 m	1000	240	280 - 285	249	80,76	22006
Type 7, 1,0 m	1000	240	285 - 290	257	81,67	22007
Type 8, 1,0 m	1000	240	290 - 295	264	82,58	22008
Type 9, 1,0 m	1000	240	295 - 300	272	83,49	22009
Type 10, 1,0 m	1000	240	300 - 305	279	85,52	22010
Type 11, 1,0 m	1000	240	305 - 310	285	86,65	22011
Type 12, 1,0 m	1000	240	310 - 315	293	87,76	22012
Type 13, 1,0 m	1000	240	315 - 320	300	88,88	22013
Type 14, 1,0 m	1000	240	320 - 325	307	90,00	22014
Type 15, 1,0 m	1000	240	325 - 330	315	91,12	22015
Type 16, 1,0 m	1000	240	330 - 335	322	92,24	22016
Type 17, 1,0 m	1000	240	335 - 340	330	93,36	22017
Type 18, 1,0 m	1000	240	340 - 345	337	94,48	22018
Type 19, 1,0 m	1000	240	345 - 350	345	95,60	22019

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGBLOC
RECYFIX®
TRAFFIC GUGBLOC

SERVICE
CHANNEL



KERBFIX 305

FASERFIX®SUPER 150

Channels

FASERFIX®SUPER 150 with ductile iron angle housings, up to load class F 900

Type 01, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	240	255	205	79,66	2400
Type 0105, 0,5 m	500	240	255	205	39,21	2449
Type 010, 1,0 m	1000	240	300	272	88,76	2442
Type 020, 1,0 m	1000	240	350	345	99,96	2444

Bolting required - see further accessories

Gratings

FASERFIX®SUPER 150, class D 400*



Ductile iron grating
SW 150/18 mm, black,
with plastic caps, 0,5 m



Ductile iron grating
SW 170/18 mm, black,
KTL-coated, with plastic caps,
locked, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating SW 150/18 mm, black, with plastic caps, 0,5 m	500	229	40	624	7,45	2463
Ductile iron grating SW 170/18 mm, black, KTL-coated, with plastic caps, locked, 0,5 m	500	229	40	624	7,45	2483
Ductile iron grating SW 150/18 mm, galvanised, with plastic caps, 0,5 m	500	229	40	624	7,44	2493

*** Not for use across the carriageway of highways or motorways in moving traffic.**

FASERFIX®SUPER 150

Gratings

FASERFIX®SUPER 150, class E 600



GUGI-Ductile iron mesh grating,
MW 15/25 mm, black,
with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
GUGI-Ductile iron mesh grating, MW 15/25 mm, black, with plastic caps, 0,5 m	500	229	40	628	11,50	2068

Solid ductile iron covers (closed) can be found in the range SERVICE CHANNELS

FASERFIX®SUPER 150, class F 900



Ductile iron grating
SW 20 mm, black,
with plastic caps, 0,5 m



Ductile iron grating
SW 20 mm, black,
KTL-coated, with plastic caps,
locked, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating SW 20 mm, black, with plastic caps, 0,5 m	500	229	40	710	9,90	2061
Ductile iron grating SW 20 mm, black, KTL-coated, with plastic caps, locked, 0,5 m	500	229	40	710	9,90	2861

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL

KERBFIX 305


FASERFIX® SUPER 150

Accessories

Trash boxes



Trash box
with galvanised bucket



	Length mm	Width mm	Height mm	Weight kg	Item No.
NEW Trash box with galvanised bucket	500	240	640	90,32	22052
Trash box with ductile iron angle housing and galvanised mud bucket	500	240	640	87,50	2452

End caps




End cap closed,
galvanised, type 01



End cap closed,
galvanised, type 010



End cap closed,
galvanised, type 020




End cap with horizontal
PVC-U pipe outlet DN/OD 160,
galvanised, type 020

	Length mm	Width mm	Height mm	Weight kg	Item No.
End cap closed, galvanised, type 01	-	240	255	0,93	2081
End cap closed, galvanised, type 010	-	240	300	1,13	2082
End cap closed, galvanised, type 020	-	240	350	1,36	2083
End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 01	-	240	255	1,05	2091
End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 010	-	240	300	1,24	2092
End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 020	-	240	350	1,70	2093


The quality of stainless steel material corresponds to CNS 1.4301.

FASERFIX® SUPER 150

Further accessories



Foul air trap
DN/OD 160



PVC-U pipe connection element
DN/OD 160



Mud bucket vertical
made of modified composite
for outlet DN/OD 160, black

	Length mm	Width mm	Height mm	Weight kg	Item No.
Hexagon bolt with locking serration, stainless steel, M 10 x 50	-	-	-	0,04	99938
Caps for hexagon bolts	24	24	7	-	91100
Foul air trap DN/OD 160	584	160	439	2,00	960
PVC-U pipe connection element DN/OD 160	-	-	-	0,50	906
NEW Mud bucket vertical made of modified composite for outlet DN/OD 160, black	-	-	-	0,13	845
Universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	0,97	19051
Tubular pistol for universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	1,30	6891
Installation aid NW 150 (exclusively for laying channels! For laying 2 pieces are necessary) - due to security reasons no return can be made	-	-	-	2,09	136018

**** Consumption for channel type 020: approx. 94 ml per joint.**

Factory-made services



Cutting to length
of NW 150



Cutting for gradient
for all nominal widths



Fixing-system EP, empty pipe
in the channel bottom,
(2 pieces per metre)

	Length mm	Width mm	Height mm	Weight kg	Item No.
Cutting to length of NW 150	-	-	-	-	991
Mitre cuts NW 150 (price per cut, two cuts necessary)	-	-	-	-	996
Cutting for gradient for all nominal widths	-	-	-	-	890
Drilling of connecting holes DN/OD 160	-	-	-	-	973
Factory-made insertion of PVC-U union connectors DN/OD 160 (incl. drilling)	-	-	-	-	983
Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)	-	-	-	0,03	703
steel bars for fixing system EP (2 pieces per metre)	-	-	-	0,01	704

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL



KERBFIX 305

FASERFIX®SUPER 200

Channels

NEW FASERFIX®SUPER 200 with galvanised angle housings, up to load class F 900

Type 01, 1,0 m





	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	290	305	362	96,77	23000
Type 0105, 0,5 m	500	290	305	362	49,00	23049
Type 01L with hole, DN/OD 200, 1,0 m*	1000	290	305	362	99,00	23035
Type 010, 1,0 m	1000	290	350	447	107,09	23042
Type 010L with hole, DN/OD 200, 1,0 m*	1000	290	350	447	114,00	23036
Type 020, 1,0 m	1000	290	400	540	113,74	23044
Type 020L with hole, DN/OD 200, 1,0 m*	1000	290	400	540	125,00	23037
Type 01 E, 1,0 m	1000	290	305	386	104,50	23105
Type 010 E, 1,0 m	1000	290	350	473	113,50	23106
Type 020 E, 1,0 m	1000	290	400	568	124,50	23107

* Position of the opening to the bottom of the channel. 200 mm from the centre of the hole (DN/OD 200) to the end of the channel.

FASERFIX®SUPER 200

NEW FASERFIX®SUPER 200 with built-in fall 0.5 %, up to load class F 900

Type 1, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 1, 1,0 m	1000	290	305 - 310	362	105,00	23001
Type 2, 1,0 m	1000	290	310 - 315	372	106,00	23002
Type 3, 1,0 m	1000	290	315 - 320	382	107,00	23003
Type 4, 1,0 m	1000	290	320 - 325	392	108,00	23004
Type 5, 1,0 m	1000	290	325 - 330	402	109,00	23005
Type 6, 1,0 m	1000	290	330 - 335	412	110,00	23006
Type 7, 1,0 m	1000	290	335 - 340	422	111,00	23007
Type 8, 1,0 m	1000	290	340 - 345	432	112,00	23008
Type 9, 1,0 m	1000	290	345 - 350	442	113,00	23009
Type 10, 1,0 m	1000	290	350 - 355	452	114,00	23010
Type 11, 1,0 m	1000	290	355 - 360	462	116,00	23011
Type 12, 1,0 m	1000	290	360 - 365	472	117,00	23012
Type 13, 1,0 m	1000	290	365 - 370	482	118,00	23013
Type 14, 1,0 m	1000	290	370 - 375	492	119,00	23014
Type 15, 1,0 m	1000	290	375 - 380	502	120,00	23015
Type 16, 1,0 m	1000	290	380 - 385	512	121,00	23016
Type 17, 1,0 m	1000	290	385 - 390	522	122,00	23017
Type 18, 1,0 m	1000	290	390 - 395	532	123,00	23018
Type 19, 1,0 m	1000	290	395 - 400	542	124,00	23019

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGBLOC
RECYFIX®
TRAFFIC GUGBLOC

SERVICE
CHANNEL


KERBFIX 305

FASERFIX®SUPER 200

Channels

FASERFIX®SUPER 200 with ductile iron angle housings, up to load class F 900

Type 01, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	290	305	362	96,72	3400
Type 0105, 0,5 m	500	290	305	362	50,21	3449
Type 010, 1,0 m	1000	290	350	447	106,54	3442
Type 020, 1,0 m	1000	290	400	540	126,42	3444

Bolting required - see further accessories

Gratings

FASERFIX®SUPER 200, class D 400*



Ductile iron grating,
SW 170/18 mm, black,
with plastic caps, 0,5 m



Ductile iron grating,
SW 170/18 mm, black,
KTL-coated, with plastic caps,
locked, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 170/18 mm, black, with plastic caps, 0,5 m	500	279	40	732	9,26	3463
Ductile iron grating, SW 170/18 mm, black, KTL-coated, with plastic caps, locked, 0,5 m	500	279	40	732	9,26	3483
Ductile iron grating SW 170/18 mm, galvanised, with plastic caps, 0,5 m	500	279	40	732	9,30	3493

*** Not for use across the carriageway of highways or motorways in moving traffic.**

FASERFIX®SUPER 200

Gratings

FASERFIX®SUPER 200, class E 600



GUGI-Ductile iron mesh grating
MW 15/25 mm, black,
with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
GUGI-Ductile iron mesh grating MW 15/25 mm, black, with plastic caps, 0,5 m	500	279	40	818	12,65	3068
GUGI-Ductile iron mesh grating, MW 15/25 mm, black, locked, KTL-coated, with plastic caps, 0,5 m	500	279	40	818	12,60	3868

Solid ductile iron covers (closed) can be found in the range SERVICE CHANNELS

FASERFIX®SUPER 200, class F 900



Ductile iron grating,
SW 20 mm, black,
with plastic caps, 0,5 m



Ductile iron grating,
SW 20 mm, black, KTL-coated,
with plastic caps, locked, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 20 mm, black, with plastic caps, 0,5 m	500	279	40	833	13,60	3061
Ductile iron grating, SW 20 mm, black, KTL-coated, with plastic caps, locked, 0,5 m	500	279	40	833	13,70	3861

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL

KERBFIX 305



FASERFIX® SUPER 200

Accessories


Trash boxes



Trash box with galvanised bucket



Trash box, 2-pieces with galvanised bucket



		Length mm	Width mm	Height mm	Weight kg	Item No.
NEW	Trash box with galvanised bucket	500	290	582	92,00	23052
NEW	Trash box, 2-pieces with galvanised bucket	500	290	900	190,50	23054
	Trash box with ductile iron angle housing and galvanised mud bucket	500	290	582	88,51	3452
	Trash box, 2-pieces with ductile iron angle housing and galvanised mud bucket	500	290	900	196,46	3454


End caps




End cap closed, galvanised, type 010



End cap closed, galvanised, type 020



End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 01




End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 020

	Length mm	Width mm	Height mm	Weight kg	Item No.
End cap closed, galvanised, type 01	-	290	305	1,35	3081
End cap closed, galvanised, type 010	-	290	350	1,58	3082
End cap closed, galvanised, type 020	-	290	400	1,79	3083
End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 01	-	290	305	1,47	3091
End cap with horizontal PVC-U pipe outlet DN/OD 160, galvanised, type 020	-	290	400	1,84	3093

FASERFIX® SUPER 200

Further accessories



PVC-Connection
DN/OD 200

	Length mm	Width mm	Height mm	Weight kg	Item No.
Hexagon bolt with locking serration, stainless steel, M 10 x 50	-	-	-	0,04	99938
Caps for hexagon bolts	24	24	7	-	91100
PVC-Connection DN/OD 200	-	-	-	0,80	907
Universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	0,97	19051
Tubular pistol for universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	1,30	6891
Installation aid NW 200 (exclusively for laying channels! For laying 2 pieces are necessary) - due to security reasons no return can be made	-	-	-	2,62	136202

**** Consumption for channel type 020: approx. 105 ml per joint.**

Factory-made services



Cutting to length
of NW 200



Cutting for gradient
for all nominal widths



Drilling of connecting holes
DN/OD 200



Factory-made insertion
of PVC-U union connectors
DN/OD 200



	Length mm	Width mm	Height mm	Weight kg	Item No.
Cutting to length of NW 200	-	-	-	-	992
Mitre cuts NW 200 (price per cut, two cuts necessary)	-	-	-	-	997
Cutting for gradient for all nominal widths	-	-	-	-	890
Drilling of connecting holes DN/OD 200	-	-	-	-	974
Factory-made insertion of PVC-U union connectors DN/OD 200	-	-	-	-	984
Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)	-	-	-	0,03	703
steel bars for fixing system EP (2 pieces per metre)	-	-	-	0,01	704

FASERFIX®SUPER 300

Channels

NEW FASERFIX®SUPER 300 with galvanised angle housings, up to load class F 900

Type 01, 1,0 m





	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	390	415	803	153,08	24000
Type 0105, 0,5 m	500	390	415	803	75,00	24001
Type 01L with outlet, DN/OD 200, 1,0 m*	1000	390	415	803	149,30	24045
Type 010, 1,0 m	1000	390	460	938	160,29	24242
Type 020, 1,0 m	1000	390	510	1088	173,11	24244
Type 01 H, 1,0 m	1000	390	630	1202	250,98	24044
Type 01 E, 1,0 m	1000	390	415	900	133,65	24105

* Position of the opening to the bottom of the channel. 200 mm from the centre of the hole (DN/OD 200) to the end of the channel.

FASERFIX®SUPER 300

NEW FASERFIX®SUPER 300 with galvanised angle housings, with built-in fall 0.5 %, up to loading class F 900

Type 1, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 1, 1,0 m	1000	390	415 - 420	811	151,00	24201
Type 2, 1,0 m	1000	390	420 - 425	826	152,00	24202
Type 3, 1,0 m	1000	390	425 - 430	841	153,00	24203
Type 4, 1,0 m	1000	390	430 - 435	856	154,00	24204
Type 5, 1,0 m	1000	390	435 - 440	871	155,00	24205
Type 6, 1,0 m	1000	390	440 - 445	886	156,00	24206
Type 7, 1,0 m	1000	390	445 - 450	901	157,00	24207
Type 8, 1,0 m	1000	390	450 - 455	916	158,00	24208
Type 9, 1,0 m	1000	390	455 - 460	931	159,00	24209
Type 10, 1,0 m	1000	390	460 - 465	946	160,00	24210
Type 11, 1,0 m	1000	390	465 - 470	961	161,00	24211
Type 12, 1,0 m	1000	390	470 - 475	976	162,00	24212
Type 13, 1,0 m	1000	390	475 - 480	991	163,00	24213
Type 14, 1,0 m	1000	390	480 - 485	1006	164,00	24214
Type 15, 1,0 m	1000	390	485 - 490	1021	165,00	24215
Type 16, 1,0 m	1000	390	490 - 495	1036	166,00	24216
Type 17, 1,0 m	1000	390	495 - 500	1051	167,00	24217
Type 18, 1,0 m	1000	390	500 - 505	1066	168,00	24218
Type 19, 1,0 m	1000	390	505 - 510	1081	169,00	24219

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGBLOC
RECYFIX®
TRAFFIC GUGBLOC

SERVICE
CHANNEL



KERBFIX 305

FASERFIX®SUPER 300

Channels

FASERFIX®SUPER 300 with ductile iron angle housings, **up to load class F 900**

Type 01, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	390	415	803	154,40	4600
Type 0105, 0,5 m	500	390	415	803	79,57	4649
Type 01H, 1,0 m	1000	390	630	1202	262,14	4644

Bolting required - see further accessories

FASERFIX®SUPER 300

Gratings


FASERFIX®SUPER 300, class C 250



Mesh grating MW 30/15 mm,
galvanised, 1,0 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Mesh grating MW 30/15 mm, galvanised, 1,0 m	1000	375	40	2127	26,08	4075
Mesh grating MW 30/15 mm, galvanised, 0,5 m	500	375	40	2127	13,31	4076

FASERFIX®SUPER 300, class D 400*



Ductile iron grating,
SW 2 x 136/18 mm, black,
with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 2 x 136/18 mm, black, with plastic caps, 0,5 m	500	377	40	1150	16,90	4563
Ductile iron grating, SW 2 x 136/18 mm, black, locked, KTL-coated, with plastic caps, 0,5 m	500	377	40	1150	16,90	4543

* Not for use across the carriageway of highways or motorways in moving traffic.

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL

KERBFIX 305

FASERFIX®SUPER 300

Gratings

FASERFIX®SUPER 300, class E 600



GUGI-Ductile iron mesh grating,
MW 15/25 mm, black,
with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
GUGI-Ductile iron mesh grating, MW 15/25 mm, black, with plastic caps, 0,5 m	500	377	40	1172	21,80	4068
GUGI-Ductile iron mesh grating, MW 15/25 mm, black, locked, KTL-coated, with plastic caps, 0,5 m	500	377	40	1172	22,50	4868

Solid ductile iron covers (closed) can be found in the range SERVICE CHANNELS

FASERFIX®SUPER 300, class F 900



Ductile iron grating,
SW 2 x 136/20 mm, black,
with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 2 x 136/20 mm, black, with plastic caps, 0,5 m	500	377	40	1334	23,20	4061
Ductile iron grating, SW 2 x 136/20 mm, black, locked, KTL-coated, with plastic caps, 0,5 m	500	377	40	1334	23,20	4861


FASERFIX® SUPER 300

Accessories

Trash boxes



Trash box,
two parts, without grating




Extension part

		Length mm	Width mm	Height mm	Weight kg	Item No.
NEW	Trash box, two parts, without grating	510	390	850	183,50	24050
NEW	Trash box, two parts, without grating, with drilling in upper body for connection of channel	510	390	850	173,89	24051
	Trash box, 2-pieces with ductile iron angle housing and galvanised mud bucket	510	390	850	216,50	4652
	Extension part	510	390	400	81,66	4054
NEW	Trash box 2-parts with PE-HD pipe, ductile iron angle housing and gate valve	510	390	850	217,00	24660

End caps



End cap closed,
galvanised, type 01




End cap with horizontal
PVC-U pipe outlet DN/OD 200,
galvanised, type 01

	Length mm	Width mm	Height mm	Weight kg	Item No.
End cap closed, galvanised, type 01	-	390	415	2,49	4081
End cap closed, galvanised, type 010	-	390	460	2,73	32973
End cap closed, galvanised, type 020	-	390	510	3,05	32974
End cap closed, galvanised, type 01H	-	390	630	3,75	4083
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 01	-	390	415	2,80	4085
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 010	-	390	460	3,27	32977
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 020	-	390	510	3,57	32978
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 01H	-	390	630	4,50	4088

FASERFIX® SUPER 300

Accessories

Further accessories



PVC-Connection
DN/OD 200

	Length mm	Width mm	Height mm	Weight kg	Item No.
Hexagon bolt with locking serration, stainless steel, M 10 x 50	-	-	-	0,04	99938
Caps for hexagon bolts	24	24	7	-	91100
PVC-Connection DN/OD 200	-	-	-	0,80	907
Universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	0,97	19051
Tubular pistol for universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	1,30	6891
Installation aid NW 300 (exclusively for laying channels! For laying 2 pieces are necessary) - due to security reasons no return can be made	-	-	-	3,66	136242

**** Consumption for channel type 01H: approx. 169 ml per joint.**

FASERFIX® SUPER 300

Factory-made services



Cutting to length of NW 300



Mitre cuts NW 300 (price per cut, two cuts necessary)



Cutting for gradient for all nominal widths



Drilling of connecting holes DN/OD 200



Factory-made insertion of PVC-U union connectors DN/OD 200



Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)

	Length mm	Width mm	Height mm	Weight kg	Item No.
Cutting to length of NW 300	-	-	-	-	993
Mitre cuts NW 300 (price per cut, two cuts necessary)	-	-	-	-	998
Cutting for gradient for all nominal widths	-	-	-	-	890
Drilling of connecting holes DN/OD 200	-	-	-	-	974
Factory-made insertion of PVC-U union connectors DN/OD 200	-	-	-	-	984
Drilling of connection holes DN/OD 315	-	-	-	-	978
Factory-made insertion of PVC-U union connectors DN/OD 315 (incl. drilling)	-	-	-	-	979
Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)	-	-	-	0,03	703
steel bars for fixing system EP (2 pieces per metre)	-	-	-	0,01	704

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGBLOC
RECYFIX®
TRAFFIC GUGBLOC

SERVICE
CHANNEL



KERBFIX 305

FASERFIX®SUPER 400

Channels

NEW FASERFIX®SUPER 400 with galvanised angle housings, up to load class F 900

Type 01, 1,0 m




	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	490	540	1383	252,00	24111
Type 01L with outlet, DN/OD 200, 1,0 m*	1000	490	540	1383	241,52	24112
Type 01H, 1,0 m	1000	490	630	1758	258,35	24116
Type 01E, 1,0 m	1000	490	540	1498	223,00	24011

* Position of the opening to the bottom of the channel. 200 mm from the centre of the hole (DN/OD 200) to the end of the channel.

FASERFIX®SUPER 400

FASERFIX®SUPER 400 with ductile iron angle housings, up to load class F 900

Type 01, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	490	540	1383	256,00	9200
Type 01H, 1,0 m	1000	490	630	1758	267,14	9244

Bolting required - see further accessories

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL

KERBFIX 305

FASERFIX®SUPER 400

Gratings

FASERFIX®SUPER 400, class D 400*



Ductile iron grating, SW 18 mm, black, with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 18 mm, black, with plastic caps, 0,5 m	500	477	40	1420	25,40	4663

* Not for use across the carriageway of highways or motorways in moving traffic.

FASERFIX®SUPER 400, class E 600



GUGI-Ductile iron mesh grating MW 15/25 mm, black, with plastic caps

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
GUGI-Ductile iron mesh grating MW 15/25 mm, black, with plastic caps	500	477	40	1634	30,00	4168

Solid ductile iron covers (closed) can be found in the range SERVICE CHANNELS

FASERFIX®SUPER 400

FASERFIX®SUPER 400, class F 900



Ductile iron grating SW 20 mm,
black, with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating SW 20 mm, black, with plastic caps, 0,5 m	500	477	40	1618	38,70	4161

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL

KERBFIX 305



FASERFIX® SUPER 400

Accessories


NEW Trash boxes



Trash box element
with galvanised mud bucket
for type 01*



Trash box element
with galvanised mud bucket
for type 01 H




	Length mm	Width mm	Height mm	Weight kg	Item No.
Trash box element with galvanised mud bucket for type 01*	1000	490	1090	847,00	24120
Trash box element with galvanised mud bucket for type 01 H	1000	490	1180	852,00	24125
Trash box 2-parts with KTL-coated ductile iron angle housing and galvanised bucket, Type 01	1000	490	1090	849,10	33265
Trash box 2-parts with KTL-coated ductile iron angle housing and galvanised bucket, Type 01 H	1000	490	1180	860,24	33266

* For positioning at the end of channel run, a closed end cap is required.

End caps



End cap closed,
galvanised, type 01




End cap with horizontal
PVC-U pipe outlet DN/OD 200,
galvanised, type 01

	Length mm	Width mm	Height mm	Weight kg	Item No.
End cap closed, galvanised, type 01	-	490	540	4,09	4091
End cap closed, galvanised, type 01H	-	490	630	4,84	4092
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 01	-	490	540	5,18	4093
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 01H	-	490	630	5,20	4097
End cap with horizontal PVC-U pipe outlet DN/OD 315, galvanised, type 01	-	490	540	5,23	42497

FASERFIX® SUPER 400

Further accessories



PVC-Connection
DN/OD 200



Installation aid NW 400 (exclusively
for laying channels! For laying 2 pieces
are necessary) - due to security reasons
no return can be made

	Length mm	Width mm	Height mm	Weight kg	Item No.
Hexagon bolt with locking serration, stainless steel, M 10 x 50	-	-	-	0,04	99938
Caps for hexagon bolts	24	24	7	-	91100
Philipp Spherical Head Lifting Clutch, 80-HKD-025, for laying trash boxes, galvanised, 4 pieces per construction site required - due to security reasons no return can be made	-	-	-	1,52	708
PVC-Connection DN/OD 200	-	-	-	0,80	907
Universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	0,97	19051
Tubular pistol for universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	1,30	6891
Installation aid NW 400 (exclusively for laying channels! For laying 2 pieces are necessary) - due to security reasons no return can be made	-	-	-	5,23	136304

**** Consumption for channel type 01H: approx. 172 ml per joint.**

Factory-made services



Cutting to length
of NW 500



Cutting for gradient
for all nominal widths



Drilling of connecting holes
DN/OD 200



Factory-made insertion
of PVC-U union connectors
DN/OD 200

	Length mm	Width mm	Height mm	Weight kg	Item No.
Cutting to length of NW 400	-	-	-	-	985
Mitre cuts NW 400 (price per cut, two cuts necessary)	-	-	-	0,01	949
Cutting for gradient for all nominal widths	-	-	-	-	890
Drilling of connecting holes DN/OD 200	-	-	-	-	974
Factory-made insertion of PVC-U union connectors DN/OD 200	-	-	-	-	984
Drilling of connection holes DN/OD 315	-	-	-	-	978
Factory-made insertion of PVC-U union connectors DN/OD 315 (incl. drilling)	-	-	-	-	979
Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)	-	-	-	0,03	703
steel bars for fixing system EP (2 pieces per metre)	-	-	-	0,01	704

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGBLOC
RECYFIX®
TRAFFIC GUGBLOC

SERVICE
CHANNEL


KERBFIX 305

FASERFIX®SUPER 500

Channels

NEW FASERFIX®SUPER 500 with galvanised angle housings, up to load class F 900

Type 01, 1,0 m




	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	590	630	2141	302,55	24121
Type 01L with outlet, DN/OD 200, 1,0 m*	1000	590	630	2141	303,70	24122

* Position of the opening to the bottom of the channel. 200 mm from the centre of the hole (DN/OD 200) to the end of the channel.

FASERFIX®SUPER 500

FASERFIX®SUPER 500 with ductile iron angle housings, up to load class F 900

Type 01, 1,0 m



	Length mm	Width mm	Height mm	Internal channel cross-sect. cm ²	Weight kg	Item No.
Type 01, 1,0 m	1000	590	630	2141	308,80	9300

Bolting required - see further accessories

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC


SERVICE
CHANNEL

KERBFIX 305

FASERFIX®SUPER 500

Gratings

FASERFIX®SUPER 500, class D 400*



Ductile iron grating, SW 18 mm,
black, with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating, SW 18 mm, black, with plastic caps, 0,5 m	500	577	40	1808	32,50	4683

* Not for use across the carriageway of highways or motorways in moving traffic.

FASERFIX®SUPER 500, class E 600




Ductile iron grating SW 20 mm,
black, with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating SW 20 mm, black, with plastic caps, 0,5 m	500	577	40	2061	45,00	4182

Solid ductile iron covers (closed) can be found in the range SERVICE CHANNELS

FASERFIX®SUPER 500

FASERFIX®SUPER 500, class F 900



Ductile iron grating SW 20 mm, black, with plastic caps, 0,5 m

	Length mm	Width mm	Height mm	Intake cross-sect. cm ² /m	Weight kg	Item No.
Ductile iron grating SW 20 mm, black, with plastic caps, 0,5 m	500	577	40	2061	46,50	4181
Ductile iron grating SW 3 x 140/20 mm, black, KTL-coated, with plastic caps, locked, 0,5 m	500	577	40	2061	41,66	5381

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGIBLOC
RECYFIX®
TRAFFIC GUGIBLOC

SERVICE
CHANNEL

KERBFIX 305


FASERFIX® SUPER 500

Accessories

NEW Trash boxes



Trash box element
with galvanised mud bucket
for type 01*




	Length mm	Width mm	Height mm	Weight kg	Item No.
Trash box element with galvanised mud bucket for type 01*	1000	590	1180	1031,00	24130
Trash box 2-parts with KTL-coated ductile iron angle housing and galvanised bucket	1000	590	1180	1031,90	33267

* For positioning at the end of channel run, a closed end cap is required.

End caps



End cap closed,
galvanised, type 01




End cap with horizontal
PVC-U pipe outlet DN/OD 200,
galvanised, type 01

	Length mm	Width mm	Height mm	Weight kg	Item No.
End cap closed, galvanised, type 01	-	590	630	5,78	4096
End cap with horizontal PVC-U pipe outlet DN/OD 200, galvanised, type 01	-	590	630	8,00	4095

FASERFIX® SUPER 500

Further accessories



PVC-Connection
DN/OD 200



Installation aid NW 500 (exclusively ,
for laying channels! For laying 2 pieces
are necessary) - due to security reasons
no return can be made

	Length mm	Width mm	Height mm	Weight kg	Item No.
Hexagon bolt with locking serration, stainless steel, M 10 x 50	-	-	-	0,04	99938
Caps for hexagon bolts	24	24	7	-	91100
Philipp Spherical Head Lifting Clutch, 80-HKD-025, for laying trash boxes, galvanised, 4 pieces per construction site required - due to security reasons no return can be made	-	-	-	1,52	708
PVC-Connection DN/OD 200	-	-	-	0,80	907
Universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	0,97	19051
Tubular pistol for universal sealant/adhesive Siga-Meltell® 320 black**	-	-	-	1,30	6891
Installation aid NW 500 (exclusively for laying channels! For laying 2 pieces are necessary) - due to security reasons no return can be made	-	-	-	6,51	136366

**** Consumption for channel type 01: approx. 184 ml per joint.**

Factory-made services



Cutting to length
of NW 500



Cutting for gradient
for all nominal widths



Drilling of connecting holes
DN/OD 200



Factory-made insertion
of PVC-U union connectors
DN/OD 200

	Length mm	Width mm	Height mm	Weight kg	Item No.
Cutting to length of NW 500	-	-	-	-	989
Mitre cuts NW 500 (price per cut, two cuts necessary)	-	-	-	0,01	959
Cutting for gradient for all nominal widths	-	-	-	-	890
Drilling of connecting holes DN/OD 200	-	-	-	-	974
Factory-made insertion of PVC-U union connectors DN/OD 200	-	-	-	-	984
Drilling of connection holes DN/OD 315	-	-	-	-	978
Factory-made insertion of PVC-U union connectors DN/OD 315 (incl. drilling)	-	-	-	-	979
Fixing-system EP, empty pipe in the channel bottom, (2 pieces per metre)	-	-	-	0,03	703
steel bars for fixing system EP (2 pieces per metre)	-	-	-	0,01	704

FASERFIX®
SUPER

FASERFIX®
KS

RECYFIX®
PLUS X

RECYFIX®
NC

RECYFIX®
MONOTEC

RECYFIX®
HICAP®F

FASERFIX®
POINT KS

FASERFIX®
TRAFFIC GUGBLOC
RECYFIX®
TRAFFIC GUGBLOC

SERVICE
CHANNEL

KERBFIX 305